

Mehrfasenstufenbohrer DIN 8374 / 8376 HSS-G

Subland drills DIN 8374 / 8376 HSS-G



Code 1625



Code 1626



Code	P			M		K				N				S
1625 · 1626	1.1 – 2.1	3.1 – 4.1	5.1	1.1 – 2.1	3.1 – 4.1	1.1 – 1.2	2.1 – 2.2	3.1 – 3.2	4.1 – 4.2	1.1 – 1.5	2.1	2.2 – 2.3	4.1 – 4.2	1.1 – 1.2

Mehrfasenstufenbohrer aus HSS zum Herstellen von exakten, zylindrischen Durchgangsbohrungen und Schraubenkopfsenkungen.

Subland drill made of HSS for producing precise, cylindrical through holes and screw head counterborings.

90° Gütegrad fein für Durchgangsloch / 90° Fine grade for through hole

M	Ø d1 mm	Ø d2 mm	L 2 mm	L 3 mm	L 1 mm		Artikel-Nr. Part-No.
M 3	3,2	6,0	9	57	93	1	1625 03 00300
M 4	4,3	8,0	11	75	117	1	1625 03 00400
M 5	5,3	10,0	13	87	133	1	1625 03 00500
M 6	6,4	11,5	15	94	142	1	1625 03 00600
M 8	8,4	15,0	19	114	169	1	1625 03 00800
M 10	10,5	19,0	23	135	191	1	1625 03 01000

180° Gütegrad mittel für Durchgangsloch / 180° Medium grade for through hole

M	Ø d1 mm	Ø d2 mm	L 2 mm	L 3 mm	L 1 mm		Artikel-Nr. Part-No.
M 3	3,4	6,0	9	57	93	1	1626 03 00300
M 4	4,5	8,0	11	75	117	1	1626 03 00400
M 5	5,5	10,0	13	87	133	1	1626 03 00500
M 6	6,6	11,0	15	94	142	1	1626 03 00600
M 8	9,0	15,0	19	114	169	1	1626 03 00800
M 10	11,0	18,0	23	135	191	1	1626 03 01000